

# ORIGINAL BIG GUN

## PLASTIC TAPER RING NOZZLES FOR THE 100 SERIES BIG GUN® SPRINKLERS

<b>12700</b> 12469 12782	<b>100TR PLASTIC CAP + BODY</b> 100TR PLASTIC CAP 100TR PLASTIC BODY	
12470-0127 12470-014 12470-016 12470-017 12470-018 12470-019 12470-020 12470-021 12470-022 12470-023 12470-024	12.7 mm TR100 PLASTIC NOZZLE 14 mm TR100 PLASTIC NOZZLE 16 mm TR100 PLASTIC NOZZLE 17 mm TR100 PLASTIC NOZZLE 18 mm TR100 PLASTIC NOZZLE 19 mm TR100 PLASTIC NOZZLE 20 mm TR100 PLASTIC NOZZLE 21 mm TR100 PLASTIC NOZZLE 22 mm TR100 PLASTIC NOZZLE 23 mm TR100 PLASTIC NOZZLE 24 mm TR100 PLASTIC NOZZLE	



### 100 TAPER RING NOZZLE – 24° TRAJECTORY – U.S. UNITS

Pressure (PSI)	12.7 mm		14 mm		16 mm		17 mm		18 mm		19 mm		20 mm		21 mm		22 mm		23 mm		24 mm	
	0.50"		0.55"		0.63"		0.67"		0.71"		0.75"		0.79"		0.83"		0.87"		0.91"		0.95"	
	GPM	RAD. (FT)	GPM	RAD. (FT)	GPM	RAD. (FT)	GPM	RAD. (FT)	GPM	RAD. (FT)	GPM	RAD. (FT)	GPM	RAD. (FT)	GPM	RAD. (FT)	GPM	RAD. (FT)	GPM	RAD. (FT)	GPM	RAD. (FT)
40	39	94	49	98	67	106	76	110	86	113	98	117	110	121	125	125	136	127	151	130	166	138
50	44	99	55	105	75	112	85	116	97	120	110	125	123	129	139	133	152	136	169	140	185	144
60	50	107	62	112	83	120	94	123	106	127	120	132	135	137	153	141	167	143	186	147	203	152
70	52	111	65	117	89	125	101	130	114	134	130	139	146	143	165	148	180	150	200	155	219	160
80	56	114	70	121	95	130	108	135	122	139	139	144	156	149	176	153	193	157	214	162	235	168
90	60	119	75	125	101	134	115	139	130	145	147	150	166	154	187	159	204	162	227	167	249	173
100	63	124	79	130	107	139	121	144	137	149	155	154	175	159	197	164	216	167	240	172	262	178
110	67	129	82	135	112	144	127	149	143	154	163	159	183	163	207	168	226	171	251	177	275	182

### 100 TAPER RING NOZZLE – 24° TRAJECTORY – METRIC UNITS

Pressure (bar)	12.7 mm			14 mm			16 mm			17 mm			18 mm			19 mm			20 mm			21 mm			22 mm			23 mm			24 mm		
	0.50"			0.55"			0.63"			0.67"			0.71"			0.75"			0.79"			0.83"			0.87"			0.91"			0.95"		
	L/S	M <sup>3</sup> /HR	RAD. (M)	L/S	M <sup>3</sup> /HR	RAD. (M)	L/S	M <sup>3</sup> /HR	RAD. (M)	L/S	M <sup>3</sup> /HR	RAD. (M)	L/S	M <sup>3</sup> /HR	RAD. (M)	L/S	M <sup>3</sup> /HR	RAD. (M)	L/S	M <sup>3</sup> /HR	RAD. (M)	L/S	M <sup>3</sup> /HR	RAD. (M)	L/S	M <sup>3</sup> /HR	RAD. (M)	L/S	M <sup>3</sup> /HR	RAD. (M)			
2.75	2.5	8.9	28.5	3.1	11.2	30.0	4.2	15.2	32.5	4.8	17.3	33.5	5.4	19.6	34.5	6.2	22.3	35.5	6.9	24.9	37.0	7.9	28.3	38.0	8.6	30.8	38.5	9.5	34.3	39.5	10.4	37.6	41.5
3	2.6	9.3	29.0	3.2	11.7	31.0	4.4	15.9	33.0	5.0	18.0	34.0	5.7	20.5	35.0	6.5	23.2	36.5	7.2	26.1	38.0	8.2	29.6	39.0	9.0	32.2	39.5	9.9	35.8	40.5	10.9	39.3	42.5
3.5	2.8	10.1	30.5	3.5	12.6	32.0	4.8	17.2	34.5	5.4	19.5	35.5	6.1	22.1	37.0	7.0	25.1	38.0	7.8	28.2	39.5	8.9	31.9	40.5	9.7	34.8	41.5	10.7	38.7	42.5	11.8	42.4	44.5
4	3.0	10.8	31.5	3.8	13.5	33.5	5.1	18.4	36.0	5.8	20.9	37.0	6.6	23.6	38.5	7.5	26.8	39.5	8.4	30.1	41.5	9.5	34.1	42.5	10.3	37.2	43.0	11.5	41.4	44.5	12.6	45.3	46.0
4.5	3.2	11.5	33.0	4.0	14.4	34.5	5.4	19.5	37.0	6.2	22.2	38.5	7.0	25.1	40.0	7.9	28.5	41.5	8.9	32.0	43.0	10.0	36.2	44.0	11.0	39.5	45.0	12.2	43.9	46.0	13.4	48.1	48.0
5	3.4	12.2	34.0	4.2	15.2	36.0	5.7	20.6	38.5	6.5	23.4	40.0	7.3	26.4	41.0	8.3	30.0	42.5	9.4	33.7	44.0	10.6	38.1	45.5	11.6	41.7	46.5	12.9	46.3	48.0	14.1	50.7	49.5
5.5	3.6	12.8	35.0	4.4	15.9	37.0	6.0	21.6	39.5	6.8	24.5	41.0	7.7	27.7	42.5	8.7	31.5	44.0	9.8	35.4	45.5	11.1	40.0	47.0	12.1	43.7	47.5	13.5	48.6	49.0	14.8	53.2	51.0
6	3.7	13.4	36.0	4.6	16.7	38.0	6.3	22.6	40.5	7.1	25.6	42.0	8.0	29.0	43.5	9.1	32.9	45.0	10.3	37.0	46.5	11.6	41.8	48.0	12.7	45.7	49.0	14.1	50.7	50.5	15.4	55.6	52.0
6.5	3.9	14.0	37.0	4.8	17.3	39.0	6.5	23.5	41.5	7.4	26.7	43.0	8.4	30.1	45.0	9.5	34.2	46.5	10.7	38.5	47.5	12.1	43.5	49.0	13.2	47.5	50.0	14.7	52.8	52.0	16.1	57.8	53.5
7	4.0	14.5	38.0	5.0	18.0	40.0	6.8	24.4	43.0	7.7	27.7	44.5	8.7	31.3	46.0	9.9	35.5	47.5	11.1	40.0	48.5	12.5	45.1	50.0	13.7	49.3	51.0	15.2	54.8	53.0	16.7	60.0	54.5
7.5	4.2	15.0	39.0	5.2	18.7	40.5	7.0	25.3	44.0	8.0	28.7	45.5	9.0	32.4	47.0	10.2	36.8	48.0	11.5	41.4	49.5	13.0	46.7	51.0	14.2	51.1	52.0	15.8	56.8	54.0	17.3	62.1	55.5

Radii are based on a 24° trajectory. The lower trajectory angles result in better wind fighting ability, but reduced throw distances. Throw reduction depends upon nozzle flow rate. In general, the throw distance is reduced approximately 3% with each 3° drop in trajectory angle. Use of the wedge insert to modify trajectory will affect distance. Big Gun® performance data has been obtained under ideal test conditions and may be adversely affected by wind, poor hydraulic entrance conditions or other factors. Test riser height of 3 feet (0.91 meters) above measurement surface. No representation regarding droplet condition, uniformity, application rate, or suitability for a particular application is made herein. Pressure refers to pressure at the nozzle.

TAPER RING NOZZLE. This nozzle combines the changeability of a Ring Nozzle with some of the efficiency of a Taper Bore Nozzle.